



BSC II SERIES FULLY AUTOMATIC CAROUSEL CLAMSHELL & BLISTER SEALING MACHINE



TYPICAL BSC II SERIES MACHINE
SHOWN WITH FEEDERS AND FINISHED PACKAGE UNLOADER

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@www.starviewpackaging.com

BSC SERIES II

FULLY AUTOMATIC ROTARY CAROUSEL CLAMSHELL & BLISTER SEALING MACHINE

YOUR MARKET ... OUR SOLUTIONS

Starview's **BSC II Series** carousel type clamshell and blister sealers are designed for high volume production requirements. Sixteen (16) station machines are standard; however, units can be manufactured with anywhere from ten (10) to twenty (20) or more stations. Standard sealing areas of 14" x 18" and 18" x 24" are offered as well as custom sizes. The standard **BSC II Series** machines feature one heated sealing station, one cooling station, one bottom blister feed station, one card feed station, one top blister feed station & one finished package unload station with the remaining positions used for operator product loading and advanced automation such as printing, vision systems, product detection, etc.

The **BSC II Series** machines may be used for Plastic-to-Plastic Clamshell sealing as well as conventional carded blisters, trapped blister packages, club style trapped blister packages, full face blisters and half-clamshell styles including certain applications using Tyvek, foils and other heat sealable lidstock.

the STARVIEW ADVANTAGE

- A wide range of standard and custom automation features available to match customer requirements.
- ANSI Class 4 machine safety for operator protection.
- Automatic blister feeder, card feeder & finished package unloader provide reduced labor costs.
- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99 databases and on-screen data tracking.
- Starview's exclusive hot/cold sealing press system allows plastic to plastic sealing of PVC, RPVC, PETG, RPETG, GAG PET, GRG PET and similar materials without the use of RF generators.
- AC Variable frequency precision cam index conveyor drive for smooth table operation and position repeatability.
- Automatic card feeder, front and back clamshell feeders & finished package unloader standard for high-volume clamshell packaging and reduced labor input.
- Industry leading design, construction, features and customer support.



more on next page

BSC SERIES II SPECIFICATIONS

	BSC II 16-1418	BSC II 16-1824
Nominal sealing area:	14" x 18"	18" x 24"
Number of open stations:	16	16
Clamshell front feeder:	7	7
Card feeder:	Standard	Standard
Clamshell back feeder:	Standard	Standard
Finished package unloader:	Standard	Standard
Max clamshell/blister depth:	Standard	Standard
Max clamshell back height:	2.5"	2.5"
Avg. cycle speed clamshell pkg:	1 – 14 cpm	1 – 12 cpm
Avg. cycle speed blister pkg:	1-18 cpm	1-14 cpm
Electrical:	208-230 Volts / 3 PH / 35 Amps	208-230 Volts / 3 PH / 50 Amps

Specifications and model availability are subject to change without notice.



REQUEST
A
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2022 Starview Packaging Machinery, Inc.

