



RP SERIES ROLLER DIE CUTTING MACHINE



RP22-1



RP28-2



RP54-2



RP40-2
SEMI-AUTOMATIC ROLLER DIE CUTTER

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@www.starviewpackaging.com

RP SERIES

ROLLER DIE CUTTING MACHINE

YOUR MARKET ... OUR SOLUTIONS

Starview's **RP Series** Roller Die Cutters are versatile enough to handle a full range of low to high production requirements. These machines will trim a wide range of materials such as skin packaged products, thermoformed products, cork, rubber and any other application where a steel rule die can be utilized.

Single driven pressure roller machines **RP-1 Series** may be used where cutting registration is not critical and cutting pressures are low. Double driven **RP-2 Series** pressure roller machines should be used where registration is important or for higher cutting pressures.

For applications where it is advantageous to cut with the product facing up or to have the ability to program cutting without manufacturing steel rule dies for each configuration please consider our **SDC Series** Slitter/Die Cutters.

the STARVIEW ADVANTAGE

- A simple and economical solution to provide steel rule die cutting for skin boards, thermoformed parts, gaskets, etc.
- Simple controls for ease of operation.
- Utilizes standard low-cost steel rule cutting dies for quick and easy changeover.
- Starview exclusive soft-start and soft-stop solid state drive system for longer system life.
- Rolls reverse for cutting in both directions to increase productivity.
- Larger than industry normal precision ground pressure rollers for minimal deflection during cutting.
- Industry leading design, construction, features and customer support.



Markets we serve everyday

more on next page

RP SERIES SPECIFICATIONS

	RP22-1
Maximum die width:	23.0"
Maximum die length:	Unlimited with support
Max die height std:	6.0"
Driven rolls:	Lower
Diameter-pressure rolls:	5.5"
Motor horsepower:	1
Average cycle speed:	1 – 4 cpm
Electrical:	208-240 Volts / 3 PH / 8 Amps

	RP28-2
Maximum die width:	29.0"
Maximum die length:	Unlimited with support
Max die height std:	6.0"
Driven rolls:	Upper & Lower
Diameter-pressure rolls:	7.5"
Motor horsepower:	2
Average cycle speed:	1 – 4 cpm
Electrical:	208-240 Volts / 3 PH / 15 Amps

	RP34-2
Maximum die width:	35.0"
Maximum die length:	Unlimited with support
Max die height std:	6.0"
Driven rolls:	Upper & Lower
Diameter-pressure rolls:	7.5"
Motor horsepower:	2
Average cycle speed:	1 – 4 cpm
Electrical:	208-240 Volts / 3 PH / 15 Amps

	RP40-2
Maximum die width:	41.0"
Maximum die length:	Unlimited with support
Max die height std:	6.0"
Driven rolls:	Upper & Lower
Diameter-pressure rolls:	7.5"
Motor horsepower:	2
Average cycle speed:	1 – 4 cpm
Electrical:	208-240 Volts / 3 PH / 15 Amps

	RP54-2
Maximum die width:	55.0"
Maximum die length:	Unlimited with support
Max die height std:	6.0"
Driven rolls:	Upper & Lower
Diameter-pressure rolls:	7.5"
Motor horsepower:	3
Average cycle speed:	1 – 4 cpm
Electrical:	208-240 Volts / 3 PH / 20 Amps

Specifications and model availability are subject to change without notice.



REQUEST
A
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2022 Starview Packaging Machinery, Inc.

